

MATERIAL SAFETY DATA SHEET

OSTREM CHEMICAL CO. LTD.
2310 - 80 AVENUE
EDMONTON AB T6P 1N2

Phone: (780) 440-1911
In Case of Emergency Only:
Phone CANUTEC: (613) 996-6666

Date completed: Oct. 1, 2008

PRODUCT NAME: MURIATIC ACID (INHIBITED) **CODE: S753**
OTHER NAME:
DISTRIBUTED BY:

WHMIS CLASSIFICATION: E; DIA
TDG CLASSIFICATION: HYDROCHLORIC ACID; Class 8; UN 1789; PG II

| HAZARDOUS INGREDIENTS | %WT/WT | CAS NO. | TOXICITY DATA (LD₅₀ & LC₅₀) |
|---------------------------------|---------------|----------------|---|
| Hydrochloric Acid (as 100% HCl) | 32 | 7647-01-0 | ACGIH TLV - 5 ppm LC ₅₀ Inhalation (rat) - 3124 ppm for 1 hour |

PHYSICAL DATA FOR PRODUCT

Physical State: Liquid
Boiling Point: 85.3°C
Vapour Density: For HCl gas 1.27
Freezing Point: Not Avail.
Solubility in Water: 100%
Appearance & Odour: Clear, slightly yellow fuming liquid with a sharp pungent irritating odour.

Sp. Gravity: 1.12
Vapour Pressure: 24 mm Hg at 20°C
pH: Strong acid < 1
Evaporation Rate: Not Avail.

FIRE AND EXPLOSION DATA FOR PRODUCT

Flash Point (Test Method): N/A
Flammable Limits in Air, % by vol. Non-flammable Lower: N/A Upper: N/A
Fire Extinguishing Substances: () Water Fog () Foam () CO₂
() Dry Chem (X) Other: Use appropriate media to extinguish surrounding fire.
Hazardous Combustion Products: Will emit toxic fumes of hydrogen chloride.

Special Firefighting Procedures: Full protective equipment, including a self contained breathing apparatus.

REACTIVITY DATA FOR PRODUCT

Incompatibility: () Water (X) Oxidizing Material () Acid (X) Base
(X) Other: High temperatures, metals.

Hazardous Decomposition Products: Reacts with most metals to produce hydrogen which may form explosive mixtures with air. When heated, hydrogen chloride is released.

Chemical Stability: Stable under normal conditions.

*N/A - Not applicable.

Product Name: **MURIATIC ACID (INHIBITED)**

HEALTH HAZARD INFORMATION FOR PRODUCT

EMERGENCY and FIRST AID PROCEDURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. Get immediate medical attention.

Ingestion: Do not induce vomiting. Unless unconscious, give 1 – 2 glasses of milk or water to dilute the material. Get immediate medical attention.

Eyes: Flush with running water for at least 20 minutes. Get medical attention immediately.

Skin: Flush with running water for at least 20 minutes. Get immediate medical attention.

EFFECTS OF OVEREXPOSURE (Acute and Chronic)

Inhalation: Irritation of the eyes, nose, throat and upper respiratory tract, coughing, choking. Extreme over exposure may lead to ulceration of the oral and nasal mucosa, pulmonary edema and possible death.

Ingestion: Severe burns to mouth, throat, esophagus and stomach; nausea, vomiting. Risk of stomach perforation, convulsions, coma & death.

Eyes: Severe burns, conjunctivitis leading to permanent damage, possible blindness.

Skin: Severe skin burns, blisters. Prolonged or repeated contact to dilute solutions may cause irritation and dermatitis.

PREVENTIVE MEASURES

Steps to be taken upon release or spillage (including neutralizing):

Remove all ignition sources. Ventilate and evacuate area. Stop and contain leak or spill. Cover with dry sand, ashes or gravel. Neutralize and dispose of in polyethylene containers. Do not allow to enter water ways. Sodium carbonate can be used as neutralizing agent.

Waste disposal method:

Consult, federal, provincial and local regulations. May be possible to flush and disperse neutralized material into drain with large amounts of water or dispose of neutralized contaminated material in a secured sanitary landfill site.

Handling and Storage Requirements:

Store in cool, dry well ventilated area in closed containers away from heat sources, metal and oxidizers.

Ventilation Requirements (Local or General): Local ventilation recommended.

Respiratory Protection: A mask should be worn.

Eye Protection: Chemical Workers goggles.

Other Protection: Impervious clothing - rubber gloves and coveralls should be worn.

Prepared by: Technical Services Department, Ostrem Chemical Co. Ltd., Ph: (780) 440-1911